

# Color Guard “Plus”

Description: Color Guard “Plus” is a unique waterbase penetrating stain/sealer, designed to be used over the Spray Deck System, that forms a tough, long lasting finish. Available in 15 beautiful colors including White and Clear seal.

## CHARACTERISTICS:

- Highly Durable
- Quick Drying
- Non-Chalking
- Flexible
- Non-Flammable
- Ultraviolet Light Resistant
- Water Resistant

## GUARD'S AGAINST:

- Tire Pick-up
- Gasoline
- Swimming Pool Additives
- Household Chemicals
- Flaking, Peeling
- Motor Oil
- Anit-Freeze

## APPLICATION:

Directions for use: (Thinning is not recommended) Ensure all deck surfaces to be coated are clean and free of pollutants or surface ambients. New concrete surfaces should be etched with 10% -20% muriatic acid, and washed thoroughly with water making sure no residue or standing water is present. Apply Color Guard “Plus” at approximately 250 square feet per gallon by roller, brush or sprayer, agitate thoroughly before use. Two coats of this product will provide the best results and durability. Allow a minimum of 48 hours for heavy traffic. Do not apply this product at temperatures below 45 degrees F or if the relative humidity is more than 90%. These conditions will effect the curing time. Concrete must be fully cured before application.

## COVERAGE:

Approximately 250 sq.ft. per gallon. Coverage rates may vary depending on substrate and atmospheric conditions.

## STORAGE:

Keep from freezing and do not store in direct sunlight.

## CLEAN UP:

Clean up with warm soapy water.

## PACKAGING:

5 gal. Pail

## SHELF LIFE:

Use within 12 months of the manufacturing date.

## WARNING:

EYE IRRITANT! During mixing or application, avoid contact with eyes. In case of such contact flood eyes repeatedly with water and CALL PHYSICIAN. Wash thoroughly after handling an before smoking or eating. Do not take internally. Harmful if swallowed. Do not induce vomiting. Call physician immediately. KEEP OUT OF REACH OF CHILDREN.

## LIMITED WARRANTY:

S.G.M., Inc. will replace any material proved defective with the maximum shelf life on unused material of up to one (1) year. If our products are not found to conform to our high standards, notify S.G.M., Inc. immediately in writing. There is no other obligation expressed or implied and we assume no liabilities for damages of any kind. Suitability of the product for an intended use shall be solely up to the user.

## SGM

**Pompano Beach, FL – Dallas, TX – Corona, CA – Plant City, FL**

Phone: 800.641.9247

1502 SW 2<sup>nd</sup> Place, Pompano Beach, FL 33069

FAX: 954.943-2402

[www.sgm.cc](http://www.sgm.cc)